



INSTALLATION INSTRUCTIONS

Dual Speaker Security Box, Part #065

Please read and fill out the enclosed warranty registration card to activate your warranty.

Tools Needed

- Electric/Battery powered drill
- 1/8" & 3/8" drill bits
- 1/2" Socket and Ratchet and 1/2" Wrench

Shipping Package

- (3) 5/16 x 1 1/4" Bolts
- (3) 5/16 Lock Nuts
- (6) 5/16" Washers
- (1) 1" Rubber Grommet

Mounting Directions

1. Place the speaker box in the mounting position and mark the vehicle directly under three of the holes in the speaker box.

Warning! Make sure that there is nothing under the vehicle that will be damaged while drilling.

2. Remove the box and, if applicable, cut out the carpet where the holes are marked.
3. Drill out the marked holes.
4. Extend the wires to the mounting location. Cut out the center of the 1" grommet and pass the wires through the grommet.
5. Fasten the speaker box to the floor using the hardware provided.
6. Put the grommet in the hole on the back of the speaker box.
7. Place the speaker cloth between the speaker and the grill then bolt the speaker to the grill.
8. Connect speaker wires to speaker.
9. Bolt the grill to the box using and special hardware provided.

Call (970) 564-1762 for Technical Support